

1. Check contents. Place the baseplate in required position on the grass making sure that it is far enough away from any obstructions for the rotating arm.
2. Mark the first hole with a screwdriver/marker. (Fig 1) Move the baseplate out of the way and push the anchor into the ground where marked.
3. Place the hammer cap over the anchor before hammering. (Fig 2)
4. Hammer the anchor into the ground, (Fig 3). When it is at ground level remove the cap.
5. Reposition the baseplate over the existing anchor, mark the position of the next anchor.
6. Repeat steps 2 to 5 until all three anchors have been installed into the ground.
7. Place the baseplate over the anchors to check position of anchors to the holes on the baseplate. If required, tap the anchor slightly to bring it back in line with the hole on the baseplate. (Fig 4)
8. Check baseplate to make sure it is level. (Fig 5) Knock the relevant anchors further into the ground if necessary to bring the plate level. (Remembering to use the hammer cap to avoid damaging the anchor top)
10. Insert the bolts over the baseplate into the top of the anchors, and tighten. (Fig 6)
11. Take the 2.5m (28mm) top pole section with the cleat and joint at the bottom, and insert it into the bottom of the vertical sleeve. (Fig 7) Push it all the way up until it comes out the top of the sleeve. (Fig 8)
7. Join the two pieces of carbon fibre rod together. Feed the carbon fibre rod into the top of the sleeve on the curved edge, black tip end first. (Fig 9)
8. Push the other end of the carbon fibre rod into the yellow connector on the arm section. (Fig 10)
9. Push the carbon rod completely into the sleeve right down to the bottom, (Fig 11) this enables you to mount the arm T joint over the vertical 28mm pole section. (Fig 12)
10. Secure the T joint on the end of the pole by tightening the grub screws with the allen key provided. (Fig 13)
11. Insert the yellow button on the end of the rope into the cleat on the pole, slide down the pole to tension the flag and tighten the wingnut. (Fig 14)
12. Add the 2.5m (45mm) bottom section onto the joint of the top section. (Fig 15) Install the pole over the spigot on the base.




Fig 1.




Fig 2.

VIEW SHOWN IS FROM
THE REVERSE OF THE
FLAG




Fig 3.




Fig 4.




Fig 5.




Fig 6.




Fig 7.




Fig 8.




Fig 9.




Fig 10.




Fig 11.




Fig 12.




Fig 13.




Fig 14.




Fig 15.



2.5m (40mm) Pole	Baseplate
2.5m (28mm) Pole (with joint and cleat attached)	3 Ground Anchors (Hammer Cap not supplied)
2 x Carbon Fibre Rods	
0.5m Arm (T joint attached)	
1 Allen Key	CONTENTS

Vision Pole Specifications

Pole Height	5m
Length of bottom section	2.5m
Inside diameter of bottom section	40.39mm
Outside diameter of bottom section	44.45mm
Length of top section	2.5m
Inside diameter of top section	25mm
Outside diameter of top section	28mm
Arm length (not incl connector or T joint)	0.5m
Arm Outside diameter	28mm
Arm Inside diameter	25mm
Length of Carbon fibre rod with joiner	1.24m
Length of Carbon fibre rod with tip	1.515m
Total weight	3.2kg
Anchor length	500mm
Anchor diameter	40mm
Anchor head size	22mm
Anchor bolt size	m12
Baseplate 'footprint diameter'	270mm
Baseplate depth	5mm
Spigot length	24mm
Spigot external diameter	40mm
Overall Baseplate height	25mm
Total Weight	6kg
Flag size	90cm x 225cm

1. TAKE DOWN POLE. NO NOT ATTEMPT TO REMOVE THE BASEPLATE WITHOUT FIRST TAKING DOWN THE POLE.
2. Undo bolts on top of the baseplate.
3. Remove the baseplate.
4. Unscrew the anchors one by one from the ground using the adjustable wrench.

WARNINGS

Remove pole from baseplate before uninstalling the plate
 Do not fly flag when wind speed exceeds Force 7 (32mph)
 It remains the responsibility of the user to establish the suitability of the product /s for the use/s to which they are put