

PRIOR TO INSTALLING WALL MOUNTED FLAGSTAFFS, WE RECOMMEND THAT YOU SEEK ADVICE REGARDING THE SUITABILITY OF THE WALL AND THE BEST TYPE OF FIXINGS FROM A PROFESSIONAL SOURCE

- 1, Check contents. Position bottom bracket ensuring that it is vertical, drill holes and bolt to the wall (see Fig 1).
- 2, Place the ground socket into the bottom bracket, ensuring it sits in the bottom of the bracket properly and level. (see Fig 2)
- 3, Centralise the top bracket vertically above the bottom bracket with the top edge of the bracket level with the top edge of the socket. Drill and fix into position. (see Fig 3).
- 4, Place weight over pole (see fig 4a), mount rotating joint onto top of pole (see fig 4b), push on finial. (see fig 4c)
If using an onion finial, push the whole final / joint assembly onto the top of pole (see fig 4d).
- 5, Push rotating arm into joint, ensure button clips into place (see fig 5a), slide top sleeve on flag over the arm. (see fig 5b)
- 6, Secure plastic ties through the eyelets and around the pole. DO NOT OVER-TIGHTEN allow a two finger space between the pole and the cable tie (see fig 6a).
At the bottom of the flag attach the D-ring to the metal clip on the weight. (see fig 6b)
- 7, Assemble the pole sections. Make sure that the joints are fully home.
8. Mount the pole into the ground socket (see Fig 7).




Fig 1.




Fig 2.




Fig 3.




Fig 4a.




Fig 4b,




Fig 4c,




Fig 4d,




Fig 5a,




Fig 5b,




Fig 6a,




Fig 6b,




Fig 7,

Flagmaster

with Wall Socket

ASSEMBLY INSTRUCTIONS

October 2019 v1

Pack 1:
2 Flagstaff sections
& Ground Socket

Pack 2:
1m Rotating Arm and ties
Rotating Joint & Finial
(or joint and Onion Finial)
Weight

Pack 3:
Top Bracket
Bottom Bracket
Ground Socket

CONTENTS

BOLTS NOT INCLUDED

Flagmaster Pole Specifications

Overall pole length (2 sections)	6.5m
Height above Ground	6.0m
Top section diameter	64mm
Length of top section	3.2m
Bottom section diameter	75mm
Length of bottom section	3.5m
Wall thickness	2.5mm
Packed Size	3.8 x 0.1 x 0.1m
Packed weight	15kg
Arm length	1m
Arm Outside diameter	20.4mm
Arm Inside diameter	17.96mm
Wall thickness	1.75mm
Weight internal diameter	85mm
Packed size	1.0 x 0.1 x 0.3m
Packed weight	2kg
Ground socket internal diameter	77mm
Ground socket external diameter	83mm
Length of ground socket	600mm
Weight	0.5kg
Bracket plate size	300mm x 100mm
Bracket internal diameter	85mm
Bolt hole diameter	14mm
Total weight of wall socket kit	4.5kg
Max flag size (portrait)	100cm x 250cm
Max flag size (portrait double sided)	100cm x 200cm

WARNINGS

Re-Usable Ties must never be over tightened

Do not fly flag when wind speed exceeds Force 7 (32mph)

It remains the responsibility of the user to establish the suitability of the product /s for the use/s to which they are put

PRIOR TO INSTALLING WALL MOUNTED FLAGSTAFFS, WE RECOMMEND THAT YOU SEEK ADVICE REGARDING THE SUITABILITY OF THE WALL AND THE BEST TYPE OF FIXINGS FROM A PROFESSIONAL SOURCE

