

Forecourt Pole

with Rotating Arm
& D-Barrier Clamp Kit

ASSEMBLY INSTRUCTIONS

October 2019 v3

1. Check contents. Open the clamp by undoing the bolt with the allen key provided.
2. Place the half with the square cut out, around the upright of the barrier (the larger aperture) and place the ground socket in the adjacent smaller aperture making sure that the bottom of the socket is on the ground. (see fig 1)
3. Place the other half of the clamp around the uprights and secure the two sections back together with the bolt. (see fig 2) Do not tighten at this stage.
4. Repeat the process with the second clamp further up the barrier upright. This must be on the vertical section, not the curved and a minimum of 25cm above the first clamp. (see fig 3)
5. Ensure that both the clamps are horizontal by using a spirit level, once level tighten up the bolts. (see fig 4)
6. Place weight over pole (see fig 5a), mount rotating joint onto top of pole (see fig 5b), push on finial. (see fig 5c)
7. Push rotating arm into joint, ensure button clips into place (see fig 6a), slide top sleeve on flag over the arm. (see fig 6b)
8. Secure plastic ties through the eyelets and around the pole. DO NOT OVER-TIGHTEN (see fig 7a). At the bottom of the flag attach the D-ring to the metal clip on the weight. (see fig 7b)
9. Mount the pole into the ground socket ensuring that the the pole reaches the bottom of the ground socket. (see fig 8)




Fig 1.




Fig 2.




Fig 3.




Fig 4.




Fig 5a.




Fig 5b.




Fig 5c.




Fig 6a.




Fig 6b.




Fig 7a.




Fig 7b.




Fig 8.

Forecourt Pole

with Rotating Arm
& D-Barrier Clamp Kit

ASSEMBLY INSTRUCTIONS

October 2019 v3



Main Ali Pole	D-Barrier Clamp Kit:
1m Rotating Arm and ties	Ground socket
Rotating Joint & Finial	Clamps x 2
Weight	Allen Key
CONTENTS	

Forecourt Pole Specifications

Pole Size	4m	5m
Length of main Aluminium section	4m	5m
Inside diameter of main Aluminium section	40.39mm	40.39mm
Outside diameter of main Aluminium section	44.45mm	44.45mm
Wall thickness	2mm	2mm
Weight internal diameter	61mm	61mm
Arm length	1m	1m
Arm Outside diameter	20.4mm	20.4mm
Arm Inside diameter	17.96mm	17.96mm
Packed Weight	4kg	5kg
Max flag size (portrait)	100cm x 250cm	100cm x 250cm
Max flag size (landscape)	180cm x 120cm	180cm x 120cm

Clamp kit Specifications

Ground Socket internal diameter	46.5mm
Ground Socket external diameter	53.5mm
Length of Ground Socket	600mm
Socket weight	0.3kg
Clamp dimensions	198mm x 100mm x 20mm
Small hole diameter	55mm
Large hole diameter	77mm
Clamp weight	1.54kg
Total Weight of kit (2 clamps + ground socket)	3.38kg

WARNINGS

Always use the clamps in conjunction with the ground socket to prevent damage to pole

Re-Usable Ties must never be over tightened

Do not fly flag when wind speed exceeds Force 7 (32mph)

It remains the responsibility of the user to establish the suitability of the product /s for the use/s to which they are put